MODEL 921

FEATURES

Increased Production and Greater Versatility

- Fast machine cycle with solenoid-operated, roller-type clutch
- Quick change feed system for different rivet sizes
- Precision machined pad on column to locate the horn at various heights
- Adaptable to a wide variety of horns and anvil holders

Reduce Down Time

- Hardened steel toggle bushings
- Needle bearing flywheel
- Enclosed belt and top lever guards
- Easy accessibility of all parts for service
- Practical parts numbering system for quick, correct replacements
- Design and construction assure life-long service

Optional Features

- Aligning, resting and clamping fixtures
- Safety guards to job specifications
- Dual palm-buttons and safety probes
- Production counters
- Compensating spring
- Choice of paint color



SPECIFICATIONS

Rivet Capacity: up to 3/8" dia. x 11/4"

Throat Depth: 12"

Stroke: 21/2" std., 3" available

Hopper: 10"

Anvil Height: 431/2"

Flywheel Speed: 175 rpm

Motor: 3/4 hp. 1140 rpm

Overall Height: 73"

Floor Space: 27" x 43"

rioor spacer 27 X is

Net Weight: 1130 lbs.



For Dependable Leadership in the Manufacturing of **Rivets**, **Rivet Machines**, **Parts and replacement Anvils**, **Drivers & Jaws**, look to our World Class Experience.